

# VERT'EX

IN A WORLD OF TRAILERS,  
TRAVIS LEADS.



## Travis® introduces its newest innovation, The Vertex.

- Available as Live Floor or as a Tipper
- Lightweight, heavy-duty, all-aluminum construction
- Aerodynamic, smooth-sided, fuel-saving design
- Dual-wall, extruded 6061-T6 aluminum
- Thin walls add 4 yards of capacity



- Heavy-duty tailgate with 3 greaseable hinges
- Lights mounted in the gate, swing out of the way
- Adjustable, manual "over-center" latches
- Flaps on gate swing out of the way
- Rubber sealed tailgate, massive top rail, and rear post
- Heavy-duty, integral push bumper

# VERT'EX



## STANDARD SPECIFICATIONS:

**BODY:** Lengths 45'-53', 96" or 102" wide, 102" tall

Aluminum Extrusions 6061-T6  
Sidewalls-dual wall, hollow core, Vertex panels with internal stiffeners  
Top Rail - 7" x 4.5" heavy duty, with shedder on top edge  
Lower Rail - 4" x 6" fully boxed tube, with integral side to floor connection  
Crossmembers - 5" x 3" flange I-Beams, on 12" centers fully welded to lower rail  
2" flat bar cross-bracing underneath floor I-Beams  
Front & Rear Posts - 9" x 7"  
Chassis Rail - 6" x 4" Z-Rail  
Tailgate - 5" x 4" Frame brace with Vertex panels  
Nose - .250 Aluminum Sheet 5454-H32

## UNDERBODY

Upper Coupler-36" Kingpin, 3/8" steel plate  
(3) 5.5" x 5" Heavy Duty Aluminum I-Beams  
Subframe - C12 x 20.7 with integrated push block  
Suspension - Reyco 21B 4-spring, 48,000 lb. capacity  
Axles - 5/8" wall, 25,000 lb. capacity, 77 1/2" track  
ABS - Wabco 4S/2M  
Hubs/Drums - Outboard Drums / Cast Hubs  
Landing Gear - Holland 2-speed  
Tires & Wheels - Radial Tires & Steel Disc Wheels

## TAILGATE

Perimeter braced, standard rubber sealed  
1.25" hinge pins  
Bolt-on, steel hinges  
(3) T-1 Steel Latch Hooks with swiveling paddle T-1 latch plates  
Manual, over center latch handle recessed in side of trailer  
(3) V-Block Gate alignment devices

## FLOOR

Floor systems from Keith Manufacturing or Hallco Industries  
Center- mounted drive huck-bolted to chassis rails & subframe  
Slats to match commodity hauled  
24 slats in 102 wide / 22 slats in 96 wide

## OTHER

DOT-approved conspicuity tape  
Sealed wiring harness  
Sealed lighting system  
Hydraulic, Air, & Electric Lines protected inside lower rail

## AVAILABLE OPTIONS:

- Tapered sidewalls 103" front to 111" rear, adds 6 yards capacity
- Rounded nose adds approximately three yards
- Remote, high lift, air operated tailgate
- Swing-in air flow gate for fuel economy
- Dual, van-style tailgate doors
- Full size access doors in the nose
- Catwalks for the nose
- Various roof options, solid or partial
- Compactor compatible center pin hook ups
- Deep kingpin settings
- Multiple axles, spread axles, air ride suspensions
- Hydraulic flip tarps, roll tarps, electric tarps
- Let us build YOUR custom features

For a dealer near you call

**Houston, Texas Factory  
and South Central**  
(800) 535-4372

**Southeast**  
(800) 622-3867

**Midwest**  
(832) 239-0042

**West, Northwest & Mountain West**  
(800) 298-2178

[info@travistrailers.com](mailto:info@travistrailers.com)  
[www.travistrailers.com](http://www.travistrailers.com)

